

METAL GUTTER SUPPORT

METAL GUTTER

FLEXCLAD METAL FASTENED 4 IN. O.C., STAGGERED USING 1-INCH GALVANIZED ANNULAR RING NAILS OR OTHER ACCEPTABLE FASTENER

FLEX TRIM STRIP, HOT-AIR WELDED

TREATED WOOD NAILERS TO MATCH HEIGHT OF INSULATION

FLEX MEMBRANE

INSULATION SECURELY FASTENED

STRUCTURAL DECK

AIR / VAPOR BARRIER (AS REQUIRED)

**NOTES:**

- 1) NAILERS SHALL BE SECURELY ANCHORED TO THE DECK TO RESIST A MINIMUM FORCE OF 300 POUNDS PER LINEAR FOOT. FOLLOW FACTORY MUTUAL LOSS PREVENTION DATA SHEET 1-49 RECOMMENDATIONS.
- 2) THE THICKNESS OF THE NAILER SHALL MATCH THE HEIGHT OF THE INSULATION OR SURFACE TO WHICH THE MEMBRANE IS TO BE APPLIED.
- 3) VAPOR BARRIER SHALL BE SEALED AT EDGES.

TITLE	FACE MOUNTED GUTTER	
NAME	DETAIL NO. 1.50	
DRAWN BY:	KF	DATE: 07/2007
APPLICABLE TO ALL FLEX		
MECHANICALLY FASTENED SYSTEMS		
FLEX MEMBRANE INTERNATIONAL	2670 LEISCZ'S BRDIGE RD. LEESPORT, PA 19533 800-969-0108 www.flexmembranes.com	