

METAL GUTTER SUPPORT

METAL GUTTER

FLEXCLAD METAL FASTENED 4 IN. O.C., STAGGERED USING 1-INCH GALVANIZED ANNULAR RING NAILS OR OTHER ACCEPTABLE FASTENER

FLEX TRIM STRIP, HOT-AIR WELDED

TREATED WOOD NAILERS TO MATCH HEIGHT OF INSULATION

FLEX PVC FIELD MEMBRANE

INSULATION SECURELY FASTENED

STRUCTURAL DECK

AIR / VAPOR BARRIER (AS REQUIRED)

NOTES:

- 1) NAILERS SHALL BE SECURELY ANCHORED TO THE DECK TO RESIST A MINIMUM FORCE OF 300 POUNDS PER LINEAR FOOT. FOLLOW FACTORY MUTUAL LOSS PREVENTION DATA SHEET 1-49 RECOMMENDATIONS.
- 2) THE THICKNESS OF THE NAILER SHALL MATCH THE HEIGHT OF THE INSULATION OR SURFACE TO WHICH THE PVC MEMBRANE IS TO BE APPLIED.
- 3) VAPOR BARRIER SHALL BE SEALED AT EDGES.

TITLE	
FACE MOUNTED GUTTER	
NAME	
DETAIL NO. 1.50	
DRAWN BY:	DATE:
KF	10/2009
APPLICABLE TO ALL FLEX PVC	
MECHANICALLY FASTENED SYSTEMS	
FLEX MEMBRANE INTERNATIONAL	2670 LEISCZ'S BRDIGE RD. LEESPORT, PA 19533 800-969-0108 FlexRoofingSystems.com