



Flex Membrane International, Inc. 2670 Leiscz's Bridge Road, Suite 400, Leesport, PA 19533 Phone: 610-916-9500 Fax: 610-916-9501

FLEX 6" TRIM STRIP

The Flex 6" Trim Strip is specifically designed to be used as a strip-in membrane for FlexClad Metal ends and joints, Flex PVC Roofing Reinforced Membrane end joint details or for patch installations. The Flex 6" Trim Strip is made out of PVC membrane for durability and longevity and reinforced for strength. Flex 6" Trim Strip is installed by the hot-air welding procedure, 2" minimum weld. The Flex 6" Trim Strip is available in roll sizes of 6" X 108'.

Physical Properties

<u>Characteristics</u>	<u>Test Method</u>	<u>Specification</u>
Colors		White, Gray or Tan
Thickness	ASTM D751	.045" Nominal
Breaking Strength	ASTM D751/D638	>340 lbs.
Elongation	ASTM D751/D638	100%
Shore "A" Hardness	ASTM D2240	83
Heat Aging	ASTM D3045	90% of Original
Cold Resistance	ASTM D2136	-40° F
Vapor Permeability	ASTM E96	3.5g./m ² /day
Weight Change	ASTM D570	1.5% maximum
Seam Strength	ASTM D751	80%
Dimensional Stability	ASTM D1204	0.5% or less
Accelerated Weathering	ASTM 2565	after 10M hours (No Change)
UL		Class A

Flex PVC Flashing Membranes are thermoplastic in nature and exceed the requirements of ASTM D4434 standard specification for Polyvinyl Chloride sheet roofing.