



## Thermoplastic Single Ply and Multi-Ply Roofing Systems

2670 Leisz's Bridge Road, Suite 400, Leesport, PA 19533 Phone (610) 916-9500 Fax (610) 916-9501

### **FLEX INSIDE AND OUTSIDE PREFABRICATED CORNERS**

#### **PHYSICAL PROPERTIES**

Color		White or Off-White
Size	<b>Inside Corner</b> <b>Outside Corner</b>	2 3/4" Height x 2 3/4" Width x 2 3/4" Depth 2 3/4" Height x 5 1/2" Width x 2 1/2" Depth
Thickness	ASTM D-638	.070" Nominal
Specific Gravity	ASTM D-792	1.32g/cm <sup>3</sup>
Tensile Strength	ASTM D-638	>2500 PSI
Elongation	ASTM D-638	>300%
Heat Aging	ASTM D-3045	90% of Original
Cold Resistance	ASTM D-1043	-400 F
Water Vapor Permeability	ASTM E-96	2.8g/m <sup>2</sup> /day
Dimensional Stability	ASTM D-1240	0.5% or less
U.V. Stability	Xenon Arc 150	10,000 hrs. Excellent

#### **METHOD OF APPLICATION**

Hot air welded to Flex flashing or field membranes.