



Thermoplastic Single Ply and Multi-Ply Roofing Systems

2670 Leisz's Bridge Road, Suite 400, Leesport, PA 19533 Phone (610) 916-9500 Fax (610) 916-9501

FLEX PREFORMED PIPE FLANGE

The Flex Preformed Pipe Flange is prefabricated for quick and easy flashing installations. The Flex Preformed Pipe Flange can be cut to fit various dimensions of 1" to 4 1/2" in diameter. The Flex Preformed Pipe Flange is installed by the hot-air welding procedure. The Flex Preformed Pipe Flange facilitates labor savings and ensures a quality installation.

CHARACTERISTICS

Property

Test Procedure

Physical Properties

Color		White, gray or tan
Size		7" in height / Fits diameters up to 4 1/2"
Thickness	ASTM D638	.125" Nominal
Specific Gravity	ASTM D792	1.32g/cm ³
Tensile Strength	ASTM D638	>2500 PSI
Elongation	ASTM D638	>300
Heat Aging	ASTM D3045	90% of Original
Cold Resistance	ASTM D1043	-40 Degrees F
Water Vapor Permeability	ASTM E96	2.8g/m ² /day
Dimensional Stability	ASTM D1240	0.5% or less
U.V. Stability	Xenon Arc 150	10,000 hrs. (Excellent)

*All Flex Preformed Pipe Flange applications require metal clamps to be installed with an approved caulking applied.