



Thermoplastic Single Ply and Multi-Ply Roofing Systems

2670 Leisch's Bridge Road, Suite 400, Leesport, PA 19533 Phone: 610-916-9500 Fax: 610-916-9501

FLEX 6" TRIM STRIP

The Flex 6" Trim Strip is specifically designed to be used as a strip-in membrane for FlexClad Metal ends and joints, Flex FB Elvaloy® Roofing Membrane end joint details or for patch installations. The Flex 6" Trim Strip is made out of DuPont Elvaloy® for membrane durability and longevity and reinforced for strength. Flex 6" Trim Strip is installed by the hot-air welding procedure, 2" minimum weld. The Flex 6" Trim Strip is available in roll sizes of 6" X 108'.

Physical Properties

<u>Characteristics</u>	<u>Test Method</u>	<u>Specification</u>
Colors		White, Gray or Tan
Thickness	ASTM D751	.045" Nominal
Breaking Strength	ASTM D751/D638	>340 lbs.
Elongation	ASTM D751/D638	100%
Shore "A" Hardness	ASTM D2240	83
Heat Aging	ASTM D3045	90% of Original
Cold Resistance	ASTM D2136	-40° F
Vapor Permeability	ASTM E96	3.5g./m ² /day
Weight Change	ASTM D570	1.5% maximum
Seam Strength	ASTM D751	80%
Dimensional Stability	ASTM D1204	0.5% or less
Accelerated Weathering	ASTM 2565	after 10M hours (No Change)
UL		Class A

Flex MF/R Flashing Membranes are thermoplastic in nature and exceed the requirements of ASTM D6754 standard specification for Polyvinyl Chloride sheet roofing.

Elvaloy® is a registered trademark of Dupont.