

VARIMAT V


Hot-air welding machine for overlap welding of roofing membranes. With digital display or the set and actual values.

- Overlap welding of PVC-P, ECB, EPDM, CSPE and TPO roofing membranes as well as elastomer bitumen
- Easy welding, also of homogenous and thin roofing membranes
- Wrinkle-free welding up to 5 m/min
- Patented pendulum pressure roller guarantees uniform pressure also on uneven surfaces
- Digital display of set and actual values of welding speed and temperature
- Constant temperature and speed independent of voltage fluctuations and ambient temperature



SPECIFICATIONS

VARIMAT 230 V

| | | |
|--------------------------|-------|---|
| Voltage | V~ | 230 |
| Power consumption | W | 4600 |
| Frequency | Hz | 50 / 60 |
| Temperature | °C | 20 - 620 |
| Speed | m/min | 0.5 - 5 |
| Welding pressure | N | 190 |
| Air flow range | % | 50 - 100 |
| Pressure static | Pa | 5000 (50 mbar) |
| Noise emission level LpA | dB | 67 |
| Welding seam width | mm | 40 |
| Size (L x W x H) | mm | 640 x 430 x 330 |
| Weight | kg | 35.0 (with 5 m cord) |
| Marking of conformity | |  |

Plastic Welding > Welding machines > VARIMAT V

Approval mark



Protection class I



VARIMAT 400 V

| | | |
|--------------------------|-------|----------------------|
| Voltage | V~ | 400 |
| Power consumption | W | 5700 |
| Frequency | Hz | 50 / 60 |
| Temperature | °C | 20 - 620 |
| Speed | m/min | 0.5 - 5 |
| Welding pressure | N | 190 |
| Air flow range | % | 50 - 100 |
| Pressure static | Pa | 5000 (50 mbar) |
| Noise emission level LpA | dB | 67 |
| Welding seam width | mm | 40 |
| Size (L x W x H) | mm | 640 x 430 x 330 |
| Weight | kg | 35.0 (with 5 m cord) |
| Marking of conformity | | |
| Approval mark | | |
| Protection class I | | |