



FLEX WALKWAY PAD

PRODUCT DESCRIPTION

Flex Walkway Pad is designed to be used as a traffic-bearing rooftop walkway on Flex's Roofing Systems. It can be used as a protection layer around rooftop equipment to protect the roofing membrane from damage. The walkway pad is manufactured in gray or safety yellow colored surfacing that has been designed to highlight traffic and maintenance areas. The traffic-bearing surface provides excellent skid resistance and the low profile does not disrupt roof drainage. Special width and length rolls are also available, as well as customer thickness and colors.

PHYSICAL PROPERTIES

Color:	Gray or Safety Yellow
Size:	2.5' wide x 60' long
Slip-Resistant Membrane Thickness:	90 mils (nominal)
Reinforcement:	1000 denier polyester
Tear Strength:	210 lbs. x 200 lbs.
Puncture Resistant:	96 pounds
Shore A Durometer:	85
Low Temperature Bend:	-40° F
Hydrostatic Resistance:	400 psi
Dimensional Stability:	less than 1%

APPLICATION

The Flex Walkway Pad is recommended to be hot air welded to the existing membrane by utilizing the hot air welding method. The Walkway Pad can also be installed with Flex Bonding Adhesive. Walkway Rolls are to be cut in lengths no longer than 10' sections, with 2" spacing between sections.